


# HIL-QUICK® Endverbinder / EV

HIL-QUICK® Close - end - terminals



halogenfrei

Nenn- querschnitt mm <sup>2</sup>	Isolierstoff Polyamid -55°C bis +125°C	Artikel-Nr.	Abmessung mm				1000 Stck. ~ kg	VE / Stück	
			$d_1$	$d_4$	$l_1$	$l_2$			
> 1 - 2,5 AWG 16 - 14		10720	2,3	5,2	16	7,0	0,800	1.250	100
> 2,5 - 6 AWG 12 - 10		10725	3,6	9,0	18	7,0	0,450	600	100
> 1 - 2,5 AWG 16 - 14		10726	2,3	8,0	21	7,0	0,900	1.000	100
> 2,5 - 4 AWG 13 - 11		10727	3,0	8,0	21	7,0	1,100	1.000	100
> 4 - 6 AWG 11 - 10		10728	3,9	10,0	26	7,5	1,600	500	100
> 6 - 8,5 AWG 10 - 8		10729	4,3	12,0	30	8,5	1,800	500	100
> 1 - 2,5 AWG 12 - 10		10730	2,3	6,0	15	7,0	0,770	1.000	100
> 2,5 - 4 AWG 12 - 10		10731	3,0	6,5	15	7,0	1,000	1.000	100
> 4 - 6 AWG 11 - 10		10732	3,9	9,2	18	8,0	1,400	1.000	100
> 6 - 8,5 AWG 10 - 8		10733	5,0	12,0	22	8,0	1,600	500	100